



SERIES ICST



Automatic rotary bottling machine for filling bottles, suitable for corrosive and non-corrosive liquids.



Technical Features

- Bottle infeed by conveyor belt
- Incoming bottle check device
- Gravity volumetric filling
- Pneumatic valves with no-drop system and Viton seals
- Bottle/liquid check device
- Continuous adjustment variable speed drive
- Bottle outfeed by conveyor belt
- Outgoing bottle check device.

Structure

Stainless steel, polyethylene, polypropylene, PVC, Hastelloyd, according to the chemical features of the product to fill. Acid proof varnish.

Optional

Bottle size changeover, bottles accumulation table.

Power

400/230/24 + compressed air.

MODEL	Filling Heads	Filling	Dosing range	Capacity l/hour	Overall dimensions			
					A	B	C	H
ICST 10/2.2 lt	10	gravity	500/2000	3000	1350	1350	1800	2400
ICST 12/2.2 lt	12	gravity	500/2000	3600	1350	1350	1800	2400
ICST 16/2.2 lt	16	gravity	500/2000	4800	1600	1600	1800	2400
ICST 20/2.2 lt	20	gravity	500/2000	6000	1750	1750	2800	2400
ICST 24/2.2 lt	24	gravity	500/2000	7500	1900	1900	2800	2400
ICST 30/2.2 lt	30	gravity	500/2000	10000	2100	2100	2800	2400
ICST 6/5 5 lt	6	gravity	1000/5000	3200	1350	1350	1800	2500
ICST 8/5 5 lt	8	gravity	1000/5000	4500	1600	1600	1800	2500
ICST 12/5 5 lt	12	gravity	1000/5000	7000	1750	1750	2800	2500
ICST 16/5 5 lt	16	gravity	1000/5000	10000	2200	2200	2800	2500

