



SERIES IPST



Rotary bottling machine for filling bottles, suitable for detergent liquids and acid detergents.



Technical Features

- Bottle infeed by conveyor belt
- Incoming bottle check device
- Pressure volumetric filling
- Stainless steel or PVC liquid valves, with Teflon seals
- Bottle/liquid check device
- Continuous adjustment variable speed drive
- Stainless steel or PVC self-priming pump
- Bottle outfeed by conveyor belt.

Structure

Stainless steel, polyethylene, polypropylene, PVC, Plexiglas, Hastelloyd, according to the chemical features of the product to fill.

Optional

Bottle size changeover, liquid dosers in Pirex glass or stainless steel, central adjustment of dosers liquid level.

Power

400/230/24 + compressed air.

MODEL	Filling Heads	Filling	Dosing range	Capacity l/hour	Overall dimensions A B C H
IPST 12/2.2 lt	12	pressure	100/2000	3600	1600 1600 1800 2400
IPST 16/2.2 lt	16	pressure	100/2000	4800	1750 1750 1800 2400
IPST 20/2.2 lt	20	pressure	100/2000	7000	2100 2100 1800 2400
IPST 24/2.2 lt	24	pressure	100/2000	9000	2300 2300 2500 2400
IPST 6/5. 5 lt	6	pressure	500/5000	3600	1600 1600 1800 2500
IPST 8/5. 5 lt	8	pressure	500/5000	4500	1600 1600 1800 2500
IPST 12/5. 5 lt	12	pressure	500/5000	7000	1850 1850 2500 2500
IPST 16/5. 5 lt	16	pressure	500/5000	10000	2300 2300 2500 2500

